

WELDED THREAD FORKS
U.N.F. (Unified National Fine)[download pdf \(50 Kb.\)](#)

High Polished Stainless Steel - AISI 316



Cat. No. RIGHT	Cat. No. LEFT	G (U.N.F.)	A (mm.)	D (mm.)	L1 (mm.)	L2 (mm.)	L3 (mm.)	Break Load (Kg.)
021206AB	031206AB	1/4"	9,5	6,35	68	13	9,8	1.300
021208AB	031208AB	5/16"	11	8	81	15	11	2.350
021210AB	031210AB	3/8"	12	9,5	94	19	14,3	3.500
021211AB	031211AB	7/16"	12	11	104	23	17,5	4.700
021212AB	031212AB	1/2"	14	12,7	119	25	18,7	5.400
021216AB	031216AB	5/8"	18	14	151	32	25	7.600
021216AXB	031216AXB	5/8"	18	16	151	33	25,1	8.000
021220AB	031220AB	3/4"	24	19	191	50,5	41	13.000
021222AB	031222AB	7/8"	30	22	224,5	57,5	46,4	17.000
021225AB	031225AB	1"	30	25,4	258	62	49,377	24.000

Note: All breakloads are determined by clevis pin and thread.
The user is responsible for choosing the proper cable diameter and for correct assembly.

[back](#)