

Series 55



RF56101



RF56121



RF56111



RF56131

20:1



Team Ronstan - Multiple 470 World champions Nathan Wilmott & Malcolm Page
Photo: Andrea Francolini / www.afrancolini.com

- ✓ RF56111 & RF56131 - Integrated becket; no loose parts.
- ✓ RF56121 & RF56131 - Composite C-Cleat and fairlead.
- ✓ Dinghy mainsheet systems.
- ✓ Multi purchase mainsheet systems on catamarans to 8m (26ft) – RF56331.
- ✓ Mainsheet systems on sportsboats using RF7 mainsheet swivel cleat unit.
- ✓ Spinnaker sheets on dinghies – especially modern asymmetric classes.

- ✓ Spinnaker sheets on sportsboats and small keel boats (lateral lead blocks).
- ✓ Control line applications on larger yachts.
- ✓ Sheave: Hard anodised Aluminium.
- ✓ Ball Bearings: High compression strength carbon black Acetal.
- ✓ Frame/Cheeks: Toughened, glass fibre reinforced Nylon.
- ✓ Rope Link: UV stabilised, multi-strand impregnated SK75 Dyneema®.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm	MAX. ROPE mm	M.W.L. kg	B.L. kg	WEIGHT g	SHEAVE DIAM. in.	MAX. ROPE in.	M.W.L. lb	B.L. lb	WEIGHT oz
RT Ratchet											
RF56101	Single, auto & manual	55	10	250	750	78	2 5/32	3/8	550	1650	2.8
RF56111	Single, becket, auto & manual	55	10	250*1	750	82	2 5/32	3/8	550*1	1650	2.9
RF56121	Single, adjustable cleat, auto	55	10	250	750	200	2 5/32	3/8	550	1650	7.1
RF56131	Single, becket, adjustable cleat, auto	55	10	250*1	750	205	2 5/32	3/8	550*1	1650	7.2

*1 Total block load. Load on becket not to exceed block load. ie. MWL 250kg (550lb), BL 750kg (1650lb). Suitable for 2:1 system at rated block load.



RF56331



RF56151A



RF56151

3 x 5mm (3/16")



RF56331B



RF2455

2 x 6mm (1/4")

- ✓ RF56331 - Low profile becket take-off under cleat arm*2.
- ✓ RF56331B - Underhung becket is suitable for terminating the sheet, or attachment of a 'piggy back' block for greater purchase*3.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.	MAX. ROPE	M.W.L.	B.L.	WEIGHT	SHEAVE DIAM.	MAX. ROPE	M.W.L.	B.L.	WEIGHT
		mm	mm	kg	kg	g	in.	in.	lb	lb	oz
RT Ratchet											
RF56331	Triple, becket, adjustable cleat, auto	55	10	750*2	1500	345	2 5/32	3/8	1650*2	3300	12.2
RF56331B	Triple, underhung becket, adjustable cleat, auto	55	10	750*3	1500	349	2 5/32	3/8	1650*3	3300	12.3
RF56151	Cheek, clockwise, auto & manual	55	10	250	700	76	2 5/32	3/8	550	1540	2.7
RF56151A	Cheek, anti-clockwise, auto & manual	55	10	250	700	76	2 5/32	3/8	550	1540	2.7
Accessories											
RF2455	Stand-up base, suits S55 BB & RT Orbit Blocks™	-	-	500	1000	26	-	-	1100	2200	0.9

*2 Total block load. Load on saddle not to exceed 15% of block load. ie. MWL 117kg (257lb), BL 234kg (514lb). Suitable for 6:1 system at rated block load.

*3 Total block load. Load on underhung becket not to exceed 33% of block load. ie. MWL 250kg (700lb), BL 500kg (1100lb). Underhung becket suits attachment of 'piggyback' block for creation of 7:1 or greater purchase.

Series 55

Photo: Chris Savage / www.kospictures.com



✓ Hole in small sheave suits becket line attachment, either direct or with Dyneema® Link.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm	MAX. ROPE mm	M.W.L. kg	B.L. kg	WEIGHT g	SHEAVE DIAM. in.	MAX. ROPE in.	M.W.L. lb	B.L. lb	WEIGHT oz
RT Ratchet											
RF56511	Fiddle*, becket, auto	55 + 35	10	250	750	108	2 5/32 + 1 3/8	3/8	550	1650	3.8
RF56531	Fiddle*, becket, adjustable cleat, auto	55 + 35	10	250	750	231	2 5/32 + 1 3/8	3/8	550	1650	8.6
Accessories											
RF2455	Stand-up base, suits S55 BB & RT Orbit Blocks™	-	-	500	1000	26	-	-	1100	2200	0.9

* Fiddle sheave has a high load full contact bearing (ie. not ball bearing). Main sheave has two-stage, ball bearing.

PRODUCT No.	BLOCKS SUITED
Dyneema® Links	
RF9004-08	S55 BB & RT single & fiddle Orbit Blocks™
RF9005-10	S55 BB & RT double & triple Orbit Blocks™
Link Retainer Clips (2 pack)	
RF50001	S55 BB & RT single & fiddle Orbit Blocks™
RF50002	S55 BB double & RT triple Orbit Blocks™