



4 x 6mm (1/4")

- ✓ High static and dynamic load capacity achieved with alloy sheaves, Torlon® needle rollers for axial loads, Acetal ball bearings for side thrust loads.
- ✓ Head posts of swivel blocks can be locked at 0° or 90°.
- ✓ Shackles are forged grade 316 stainless steel.
- ✓ Cheek cut-outs for easy bearing maintenance.
- ✓ Removable becket allow lines to be spliced prior to fitting.
- ✓ Halyard block has a removable pin for attachment to deck padeyes, mast collar or mainsail headboard.
- ✓ Mainsheet on boats to 14m (46ft).
- ✓ Halyard and Spinnaker sheets on boats to 15m (50ft).
- ✓ Permanent backstay applications on boats to 11m (36ft).
- ✓ General control line applications on larger yachts.
- ✓ Alloy sheave and cheek plates.
- ✓ Torlon® needle rollers.
- ✓ Carbon black Acetal ball bearings.
- ✓ Grade 316 stainless steel head post and forged shackle.

PRODUCT No.	DESCRIPTION	SHEAVE	MAX.	PIN	M.W.L.	B.L.	WEIGHT	SHEAVE	MAX.	PIN	M.W.L.	B.L.	WEIGHT
		DIAM.	ROPE	DIAM.	kg	kg	g	DIAM.	ROPE	DIAM.	lb	lb	oz
		mm	mm	mm				in.	in.	in.			
RB Roller Ball Bearing													
RF78100	Single block	75	14	8	1990	3980	475	3	9/16	5/16	4390	8770	16.8
RF78108	Halyard block	75	14	10	1660	3320	298	3	9/16	3/8	3660	7320	10.5
RF78110	Single block, becket	75	14	8	1990	3980	530	3	9/16	5/16	4390	8770	18.7
RF78140	Stand-up block	75	14	-	1990	3980	576	3	9/16	-	4390	8770	20.3
RF78202	Double, non-swivel head	75	14	-	1990	3980	640	3	9/16	-	4390	8770	22.6
AP All Purpose													
RF71100	Single block	75	14	8	1500	3980	441	3	9/16	5/16	3310	8770	15.6
RF78108	Halyard block	75	14	8	1500	3980	282	3	9/16	5/16	3310	8770	10.0