

# Foot Blocks

5 x 6mm (1/4")



RF60151

5 x 6mm (1/4")



RF60251

3 x 8mm (5/16")



RF61151

AP



RF68151

3 x 8mm (5/16")



RF68251



RF1391

2 x 8mm (5/16")  
1 x 10mm (3/8")



RF71151

AP



RF78151

2 x 8mm (5/16")  
1 x 10mm (3/8")



RF78251

✓ Footblocks are available in single or double versions, with through-hub mounting for maximum strength.

✓ Check cut-outs for easy bearing maintenance.

| PRODUCT No.                   | DESCRIPTION  | SHEAVE DIAM. mm | MAX. ROPE mm | M.W.L. kg | B.L. kg | WEIGHT g | SHEAVE DIAM. in. | MAX. ROPE in. | M.W.L. lb | B.L. lb | WEIGHT oz |
|-------------------------------|--|-----------------|--------------|-----------|---------|----------|------------------|---------------|-----------|---------|-----------|
| <b>BB Ball Bearing</b>        |  |                 |              |           |         |          |                  |               |           |         |           |
| RF60151                       | Foot block, single   | 60              | 10           | 600       | 1500    | 116      | 2 3/8            | 3/8           | 1320      | 3310    | 4.1       |
| RF60251                       | Foot block, double   | 60              | 10           | 600*      | 1500*   | 172      | 2 3/8            | 3/8           | 1320*     | 3310*   | 6.1       |
| <b>RB Roller Ball Bearing</b> |  |                 |              |           |         |          |                  |               |           |         |           |
| RF68151                       | Foot block, single   | 60              | 14           | 1500      | 3000    | 194      | 2 3/8            | 9/16          | 3310      | 6610    | 6.8       |
| RF68251                       | Foot block, double   | 60              | 14           | 1500*     | 3000*   | 291      | 2 3/8            | 9/16          | 3310*     | 6610*   | 10.3      |
| RF78151                       | Foot block, single   | 75              | 14           | 2200      | 4400    | 304      | 3                | 9/16          | 4850      | 9700    | 10.7      |
| RF78251                       | Foot block, double   | 75              | 14           | 2200*     | 4400*   | 536      | 3                | 9/16          | 4850*     | 9700*   | 18.9      |
| <b>AP All Purpose</b>         |  |                 |              |           |         |          |                  |               |           |         |           |
| RF61151                       | Foot block, single   | 60              | 14           | 1000      | 3000    | 178      | 2 3/8            | 9/16          | 2200      | 6610    | 6.3       |
| RF71151                       | Foot block, single   | 75              | 14           | 1500      | 3980    | 295      | 3                | 9/16          | 3310      | 8770    | 10.4      |
| <b>Accessories</b>            |  |                 |              |           |         |          |                  |               |           |         |           |
| RF1391                        | Jammer kit, suits RF61151, RF68151, RF68251, RF71151, RF78151, RF78251, RF108151, RF108251 | -               | -            | -         | -       | 90       | -                | -             | -         | -       | 3.2       |

\* Total block load. Maximum load on top sheave not to exceed 50% of total block load.

# Foot Blocks

5 x 8mm (5/16")



RF108151

5 x 8mm (5/16")



RF108251

5 x 10mm (3/8")



RF128151

5 x 10mm (3/8")



RF128251

2 x 12mm (7/16")  
1 x 10mm (3/8")



RF158151

2 x 12mm (7/16")  
6 x 10mm (3/8")



RF158251

✓ Footblocks are available in single or double versions, with through-hub mounting for maximum strength.

- Alloy sheave and cheek plates.
- Torton® needle rollers.
- Carbon black Acetal ball bearings.

| PRODUCT No.                   | DESCRIPTION        | SHEAVE DIAM. mm | MAX. ROPE mm | M.W.L. kg | B.L. kg | WEIGHT g | SHEAVE DIAM. in. | MAX. ROPE in. | M.W.L. lb | B.L. lb | WEIGHT oz |
|-------------------------------|--------------------|-----------------|--------------|-----------|---------|----------|------------------|---------------|-----------|---------|-----------|
| <b>RB Roller Ball Bearing</b> |                    |                 |              |           |         |          |                  |               |           |         |           |
| RF108151                      | Foot block, single | 100             | 14           | 3850      | 7890    | 480      | 4                | 9/16          | 8490      | 17390   | 16.9      |
| RF108251                      | Foot block, double | 100             | 14           | 3850*     | 7890*   | 850      | 4                | 9/16          | 8490*     | 17390*  | 30.0      |
| RF128151                      | Foot block, single | 125             | 16           | 4900      | 9800    | 850      | 5                | 5/8           | 10800     | 21610   | 30.0      |
| RF128251                      | Foot block, double | 125             | 16           | 4900*     | 9800*   | 1520     | 5                | 5/8           | 10800*    | 21610*  | 53.6      |
| RF158151                      | Foot block, single | 150             | 20           | 6900      | 13800   | 1483     | 6                | 3/4           | 15210     | 30420   | 52.3      |
| RF158251                      | Foot block, double | 150             | 20           | 6900*     | 13800*  | 2642     | 6                | 3/4           | 15210*    | 30420*  | 93.2      |

\* Total block load. Maximum load on top sheave not to exceed 50% of total block load.