

# Deck Organisers



- ✓ Deck organisers are an effective means of deflecting halyards and control lines to winches, stoppers and cleats.
- ✓ All-purpose bearing system provides maximum static load capacity.
- ✓ Light weight design with check cut-outs for easy bearing maintenance.
- ✓ Through-hub mounting for maximum strength.
- ✓ All sizes can be stacked to create double versions - M.W.L. of the top sheaves must not exceed 50% of the total block load rating.

- Series 40 - halyard and control line deflection on boats to 11m (36ft).
- Series 60 - halyard and control line deflection on boats to 14m (46ft).
- Line deflection on larger yachts (depending on load and angle of deflection).
- Alloy upper and lower cheek plates.
- U.V. stabilised Acetal sheaves.
- Grade 316 stainless steel hubs.

PRODUCT No.	DESCRIPTION	SHEAVE	MAX.	HOLE	M.W.L.	B.L.	WEIGHT	SHEAVE	MAX.	HOLE	M.W.L.	B.L.	WEIGHT		
		DIAM.	ROPE	LENGTH	SPACING	(per sheave)		(per sheave)	DIAM.	ROPE	LENGTH	SPACING		(per sheave)	(per sheave)
		mm	mm	mm	mm	kg	kg	in.	in.	in.	in.	in.	lb	lb	oz
RF41811	Cheek block, aluminium cheeks	40	12	67	-	400	1000	65	1 9/16	1/2	2 5/8	-	880	2200	2.3
RF41821	Double sheave organiser	40	12	116	48.5	500	1000	101	1 5/8	1/2	4 9/16	1 29/32	1100	2200	3.6
RF41831	Triple sheave organiser	40	12	164	48.5	500	1000	142	1 5/8	1/2	6 15/32	1 29/32	1100	2200	5.0
RF41841	Quadruple sheave organiser	40	12	213	48.5	500	1000	185	1 5/8	1/2	8 13/32	1 29/32	1100	2200	6.5
RF51151	Cheek block	50	12	75	-	500	1000	85	2	1/2	2 15/16	-	1100	2200	3.0
RF61821	Double sheave organiser	60	14	164	70.0	1000	2000	271	2 3/8	9/16	6 15/32	2 3/4	2200	4410	9.6
RF61831	Triple sheave organiser	60	14	234	70.0	1000	2000	392	2 3/8	9/16	9 7/32	2 3/4	2200	4410	13.8
RF61841	Quadruple sheave organiser	60	14	304	70.0	1000	2000	511	2 3/8	9/16	11 31/32	2 3/4	2200	4410	18.0
<b>Accessories</b>															
RF51153	Curved surface adapter for RF51151	-	-	-	-	-	-	14	-	-	-	-	-	-	0.5