

Series 75



RF1088
RF1088AW



RF1096



RF1089



RF1097



RF617
6.4mm (1/4") pin

- ✓ Self-lubricating Oilite® bronze bearing on a stainless steel race minimises friction and ensures extreme durability.
- ✓ Bolt-through construction allows for servicing and sheave replacement or upgrade to alloy version.
- ✓ High static and dynamic load capacity.

- ✓ Aluminium sheave versions (AW suffix) are suitable for use with wire.
- ✓ Universal head can be fixed at 0 or 90°, or left free to swivel.
- ✓ Black chromed stainless steel cheeks are flared at the rope entry and exit points to minimise chafing.
- ✓ Jib lead slide with pin stop suits RC7320 32mm (1 1/4") T-track.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm	MAX. ROPE mm	MAX. WIRE mm	PIN DIAM. mm	M.W.L. kg	B.L. kg	WEIGHT g	SHEAVE DIAM. in.	MAX. ROPE in.	MAX. WIRE in.	PIN DIAM. in.	M.W.L. lb	B.L. lb	WEIGHT oz
RF1088	Single block, universal head	75	14	-	7.9	1500	3000	480	3	9/16	-	5/16	3300	6600	17.1
RF1088AW	Single block, alum. rope/wire sheave, universal head	75	14	8	7.9	1500	3000	520	3	9/16	5/16	5/16	3300	6600	18.4
RF1089	Single block, becket, universal head	75	14	-	7.9	1500	3000	529	3	9/16	-	5/16	3300	6600	18.6
RF1096	Double block, universal head	75	14	-	7.9	1500	3000	700	3	9/16	-	5/16	3300	6600	24.7
RF1097	Double block, becket, universal head	75	14	-	7.9	1500	3000	780	3	9/16	-	5/16	3300	6600	27.5

AP All Purpose



RF618
7.9mm (5/16") pin

4 x 6mm (1/4")

- ✓ Bolt-head block RF1080 provides a compact solution where full articulation of the block isn't required.
 - ✓ Stand-up block RF1100 features a diamond shaped deck plate for close positioning when fitted around the mast base for halyard leads, and has a swivel head post to allow full articulation and rotation.
 - ✓ Mainsheet, halyard and spinnaker sheets on boats to 14m (46ft).
 - ✓ General applications on larger yachts.
- U.V. stabilised Acetal sheaves.
 - Aluminium sheave ("AW" versions).
 - Black chromed grade 316 stainless steel cheeks.
 - Grade 316 stainless steel load straps and head fittings.

PRODUCT No.	DESCRIPTION	SHEAVE	MAX.	MAX.	PIN	M.W.L.	B.L.	WEIGHT	SHEAVE	MAX.	MAX.	PIN	M.W.L.	B.L.	WEIGHT
		DIAM.	ROPE	WIRE	DIAM.	kg	kg	g	DIAM.	ROPE	WIRE	DIAM.	lb	lb	oz
		mm	mm	mm	mm				in.	in.	in.	in.	lb	lb	oz
RF891	Single block, snap shackle head	75	14	-	-	1500	3000	545	3	9/16	-	-	3300	6600	19.2
RF1080	Single block, bolt head	75	14	-	-	1500	4000	345	3	9/16	-	-	3300	8800	12.2
RF1082	Triple block, universal head	75	14	-	7.9	1500	3000	905	3	9/16	-	5/16	3300	6600	31.9
RF1100	Stand-up block	75	14	-	-	1500	3000	520	3	9/16	-	-	3300	6600	18.3