








Wire Blocks, Sheave Boxes & Upright Lead Blocks



-  Wire blocks have purpose designed narrow sheaves and grooves.
-  Upright lead blocks are a low profile solution for leading lines to cleats or jammers.
-  Sheave boxes are ideal for applications where lines (rope or wire) need to be led through decks, bulkheads or spars minimising friction and chafing.

-  Wire blocks suit halyards, vang and backstay applications.
-  U.V. stabilised Acetal sheaves.
-  Nylatron® sheaves (wire blocks and sheave boxes).
-  Grade 316 stainless steel cheeks.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM.	MAX. WIRE	M.W.L.	B.L.	WEIGHT	SHEAVE DIAM.	MAX. WIRE	M.W.L.	B.L.	WEIGHT
		mm	mm	kg	kg	g	in.	in.	lb	lb	oz
Wire Blocks											
RF103	Single block, tubular rivet head, removable sheave	45	6	850	1700	88	1 3/4	1/4	1870	3740	3.1
RF104	Single block, ferrule top, removable sheave	45	6	850	1700	80	1 3/4	1/4	1870	3740	2.8
RF418	Single block, tubular rivet head	25	3	450	900	40	1	1/8	990	1980	1.4
RF418C	Single block, removable clevis pin head	25	3	450	900	39	1	1/8	990	1980	1.4
RF468	Single block, ferrule top, removable sheave	32	3	450	900	33	1 1/4	1/8	990	1980	1.2
RF560	Single block, ferrule eye	19	3	250	500	20	3/4	1/8	550	1100	0.7
RF667	Single block, loop top	19	2	200	400	20	3/4	3/32	440	880	0.7

PRODUCT No.	SHEAVE DIAM.	MAX. ROPE	MAX. WIRE	A	B	C	D	M.W.L.	B.L.	WEIGHT	SHEAVE DIAM.	MAX. ROPE	MAX. WIRE	A	B	C	D	M.W.L.	B.L.	WEIGHT
	mm	mm	mm	mm	mm	mm	mm	kg	kg	g	in.	in.	in.	in.	in.	in.	in.	lb	lb	oz
Sheave Boxes																				
RF452	22	3	3	25.5	26	7.5	5	160	320	30	7/8	1/8	1/8	1	1	5/16	3/16	350	700	1.1
RF31712	30	8	4	44.0	27	14.0	5	375	800	45	1 3/16	5/16	5/32	1 3/4	1 1/16	9/16	3/16	830	1760	1.6
RF41712	40	10	5	54.0	33	17.0	5	500	1000	75	1 9/16	3/8	3/16	2 1/8	1 5/16	11/16	3/16	1100	2200	2.6
RF51712	50	12	5	62.0	42	21.0	5	800	1500	145	2	1/2	3/16	2 7/16	1 5/8	13/16	3/16	1760	3300	5.1

PRODUCT No.	SHEAVE DIAM.	MAX. ROPE	MAX. WIRE	M.W.L.	B.L.	WEIGHT	SHEAVE DIAM.	MAX. ROPE	MAX. WIRE	M.W.L.	B.L.	WEIGHT
	mm	mm	mm	kg	kg	g	in.	in.	in.	lb	lb	oz
Upright Lead Blocks												
RF453	22	3	3	160	320	30	7/8	1/8	1/8	350	700	1.1
RF568	19	5	-	250	500	20	3/4	3/16	-	550	1100	0.7
RF569	19	8	-	250	500	20	3/4	5/16	-	550	1100	0.7
RF917	19	8	-	250	500	20	3/4	5/16	-	550	1100	0.7
RF919	29	6	-	600	1200	50	1 3/32	1/4	-	1320	2640	1.8
RF2379	13	5	-	250	500	20	19/32	3/16	-	550	1100	0.7
RF2416	32	5	-	300	800	40	1 1/4	3/16	-	660	1760	1.4