



**TRACK FASTENINGS** – 4mm (5/32") countersunk fasteners at 50mm (1 31/32") centres

- ✓ Low profile, lightweight alloy cars and end caps.
- ✓ Twin rows of recirculating Torlon® ball bearings provide smooth, low friction performance under load.
- ✓ Loop and fork style fittings are easily added for becket and control line block attachment.
- ✓ Compact sheave arrangements for neat, low profile control line purchase systems. Control sheaves are 24mm (15/16") diameter and suit up to 6mm (1/4") rope.
- ✓ Cleats, fairleads and cheek blocks can be mounted directly on deck or cockpit sides to complete the control line systems.
- ✓ Dinghy and catamaran traveller and jib sheet systems.
- ✓ Alloy track, car bodies and end caps.
- ✓ Torlon® ball bearings.
- ✓ Grade 316 stainless steel fixtures.

PRODUCT No.	DESCRIPTION	LENGTH	WIDTH	M.W.L.	B.L.	WEIGHT	LENGTH	WIDTH	M.W.L.	B.L.	WEIGHT
		mm	mm	kg	kg	g	in.	in.	lb	lb	oz
<b>BB Ball Bearing</b>											
RC1141J	Track joiner	40	-	-	-	1	1 9/16	-	-	-	0.1
RC11401	Car, 2 mounting holes, 35mm (1 3/8") hole spacing	68	41	150	400	51	2 11/16	1 5/8	330	880	1.8
RC11402	Car, pivoting shackle top	47	41	125	400	48	1 7/8	1 5/8	280	880	1.7
RC11403	Car, pivoting shackle top, 2 mounting screws	78	41	180	400	91	3 1/16	1 5/8	400	880	3.2
RC1140-1.0*	Track, black	996	14	-	-	230	39 1/4	9/16	-	-	8.1
RC1140-1.5*	Track, black	1496	14	-	-	345	59	9/16	-	-	12.2
RC1140-2.0*	Track, black	1996	14	-	-	460	78 5/8	9/16	-	-	16.2
RC1140-3.0*	Track, black	2996	14	-	-	690	118	9/16	-	-	24.3
RC1140-6.0*	Track, black	5996	14	-	-	1380	236 1/4	9/16	-	-	48.7
RC11410	Car, saddle top, single control sheaves	68	41	150	400	89	2 11/16	1 5/8	330	880	3.1
RC11480	End cap, plastic	28	20	-	-	6	1 1/8	25/32	-	-	0.2
RC11484	Control end, single sheave	52	33	-	-	15	2	1 5/16	-	-	0.5
RC11485	Control end, single sheave & becket	64	33	-	-	23	2 1/2	1 5/16	-	-	0.8
<b>Accessories</b>											
RF134	Saddle, control line termination point	-	-	-	-	5	-	-	-	-	0.2
RF1050	Control becket, 8mm (5/16") eye, suits RC11403	-	-	-	-	6	-	-	-	-	0.2
RF1052	Control becket fork, 5mm (3/16") pin, suits RC11403	-	11	-	-	9	-	7/16	-	-	0.3
RF5000	Cleat, suits 2mm - 8mm (3/32" - 5/16") rope	-	-	75	150	20	-	-	165	330	0.7
RF5005	Fairlead, suits RF5000 cleat	-	-	-	-	7	-	-	-	-	0.2
RF20151	Cheek block, for leading control lines	-	-	250	550	14	-	-	550	1210	0.5
RF20151A	Cheek block rivet mount, for leading control lines	-	-	200	550	17	-	-	440	1210	0.6

\* Silver track available - order a RCxxxxxxS