



Hand Swage Fittings




THIMBLE




SAILMAKER THIMBLE



COPPER FERRULE




WIRE ROPE GRIP




- ✓ Copper ferrules are nickel plated for aesthetic appearance and long-term weather resistance.
- ✓ Stainless steel wire rope grips require no special tools for assembly and can be disassembled and reused.

WIRE CUTTERS



HAND SWAGE TOOLS



PRODUCT No.	RECOMMENDED WIRE DIAM. mm	A mm	B mm	C mm	WEIGHT g	RECOMMENDED WIRE DIAM. in.	A in.	B in.	C in.	WEIGHT oz
RF481	2.5	9.0	3.0	16	2	3/32	11/32	1/8	5/8	0.1
RF482	3.0	10.0	4.0	18	2	1/8	3/8	5/32	23/32	0.1
RF483	4.0	11.0	5.0	19	5	5/32	7/16	3/16	3/4	0.2
RF484	5.0	13.0	6.0	23	5	3/16	1/2	1/4	29/32	0.2
RF485	6.0	15.0	7.5	28	15	1/4	19/32	9/32	1 1/8	0.5
RF486	8.0	21.0	10.5	38	25	5/16	13/16	13/32	1 1/2	0.9
RF487	10.0	27.0	11.5	53	40	3/8	1 1/16	7/16	2 1/16	1.4
RF2488	12.0	29.0	15.5	55	65	1/2	1 1/8	5/8	2 3/16	2.3
RF2490	16.0	40.0	20.0	67	125	5/8	1 9/16	25/32	2 5/8	4.4
RF2492	19.0	51.0	22.0	87	275	3/4	2	7/8	3 7/16	9.7
RF2494	26.0	65.0	29.0	115	615	1	2 1/2	1 1/8	4 1/2	21.7
Sailmaker Thimbles - Stainless Steel										
RF2180	3.0	9.0	4.5	16	3	1/8	11/32	3/16	5/8	0.1
RF2181	4.0	11.0	5.5	20	5	5/32	7/16	7/32	25/32	0.2
RF2182	5.0	17.0	6.3	27	10	3/16	21/32	1/4	1 1/16	0.4
RF2183	6.0	21.0	8.5	33	20	1/4	13/16	11/32	1 5/16	0.7
RF2184	8.0	26.0	11.0	40	40	5/16	1	7/16	1 9/16	1.4
Copper Ferrules										
RF3169	1.5	8.0	-	-	2	1/16	5/16	-	-	0.1
RF3170	2.0	10.0	-	-	2	5/64	3/8	-	-	0.1
RF3171	2.5	11.0	-	-	3	3/32	7/16	-	-	0.1
RF3172	3.0	14.0	-	-	5	1/8	9/16	-	-	0.2
RF3173	4.0	18.5	-	-	10	5/32	23/32	-	-	0.4
RF3174	5.0	19.0	-	-	15	3/16	3/4	-	-	0.5
RF3175	6.0	20.0	-	-	22	1/4	25/32	-	-	0.8
Wire Rope Grips										
RF1685-2	2.0	13.7	14.0	18	10	5/64	9/16	23/32	11/16	0.3
RF1685-4	4.0	18.0	18.0	24	20	5/32	11/16	23/32	15/16	0.7
RF1685-5	5.0	18.2	20.0	28	30	3/16	11/16	13/16	1 1/8	1.0
RF1685-6	6.0	21.3	21.0	33	40	1/4	13/16	27/32	1 9/32	1.4
RF1685-8	8.0	27.2	24.0	43	80	5/16	1 1/16	15/16	1 5/8	2.8
RF1685-10	10.0	31.6	34.0	51	140	3/8	1 7/8	1 5/16	2	4.9
RF1685-12	12.0	37.7	36.0	65	220	1/2	1 1/2	1 7/16	2 9/16	7.7

PRODUCT No.	LENGTH mm	TO SUIT WIRE mm	WEIGHT g	LENGTH in.	TO SUIT WIRE in.	WEIGHT oz
CLA606	200	1-4	310	8	3/64-5/32	10.9
CLA609	330	1-6	720	13	3/64-1/4	25.4
Hand Swage Tools						
CLA731	300	1, 1.5, 2, 2.5	730	12	3/64, 1/16, 5/64, 3/32	25.7
CLA763	600	2, 2.5, 3	2300	24	5/64, 3/32, 1/8	81.1
CLA774	750	3, 4	3980	30	1/8, 5/32	140.6
CLA775	750	4, 5	3960	30	5/32, 3/16	139.7
CLA776	750	6	3930	30	1/4	138.6